

## SIMPLY UNIVERSAL

# GNP-VN4

## VANDAL RESISTANT FIXTURE



### Description /Application

Large die cast aluminum vandal resistant fixture with powder coat finish, white powder coat steel reflector, and clear prismatic polycarbonate lens. Can be used with our Quick-Mount bracket!

### Specification Features

- CSA listed for wet locations.
- Vandal Resistant Fixture.
- Custom colors available upon request.
- Specifications subject to change without notice.

### Housing:

Die Cast Aluminum Housing, 1/2 Coin Plugs with O-rings for Conduit & Photocell on Two Sides & Back, Textured Architectural Bronze Powdercoat Finish Over a Chromate Conversion Coating.

### Lens:

Clear Prismatic Polycarbonate Lens


### Mounting:

Mount Directly Over a 4 Recessed Outlet Box, or use 1/2 Surface Conduit or Quick-Mount Bracket.

### Listing & Ratings:

CSA: Listed for Wet Locations

Custom Colors Available Upon Request.



### INTENSITY (CANDLEPOWER) SUMMARY

ANGLE	MEAN CP	LMS.	ANGLE	MEAN CP	LMS.
0	1216		90	29	
5	1211	117	95	2	7
10	1199		100	0	
15	1181	333	105	0	0
20	1155		110	0	
25	1122	517	115	0	0
30	1082		120	0	
35	1032	645	125	0	0
40	972		130	0	
45	898	691	135	0	0
50	811		140	0	
55	708	631	145	0	0
60	594		150	0	
65	477	473	155	0	0
70	366		160	0	
75	257	270	165	0	0
80	148		170	0	
85	70	84	175	0	0
90	29		180	0	

### ZONAL LUMENS AND PERCENTAGES

ZONE	LUMENS	% LUMINAIRE
0-30	967	25.68
0-40	1612	42.79
0-60	2933	77.88
0-90	3760	99.83
40-90	2148	57.03
60-90	827	21.95
90-180	7	0.17
0-180	3767	100.00

EFFICAY (LUMENS PER WATT): 78.8  
THIS IS AN ABSOLUTE TEST

